Senior Shinobi NVR Stack configuration when getting new Gateway / Firewall

DNS

Freenom DNS records updated to new public IP

Ports Forwarded

If on Xfi Gateway this has to be done on xfinity mobile app. This is unfortunately the case for new XFI gateways.

80/tcp, 443/tcp, and 51820/tcp have to be forwarded to the server and has to done under the same IP.

Multiple ports can be added to the same IP in the XFi app so don't worry

IP Reservation

Reserved IPs are still configured on 10.0.0.1. Default login is admin //// password

Assign these IPs to the Cameras

```
UIDCAM4 = 10.0.0.71
UIDCAM3 = 10.0.0.16
UIDCAM2 = 10.0.0.253
UIDCAM1 = 10.0.0.242
```

Check Reolink Client App

Make sure all FTP Surveillance is working and that all Cameras have a video feed.

IP Addresses reserved must match.

> As of 2023.10.01 all 4 camera IPs are set as static IPs. On new comcast gateways they should retain the same internal IPs.

Shinobi Web App

Make sure each camera has the same reserved IPs.

Bonus

Fix client Wireguard config IP address range to 10.0.0.0/24

Update client Wireguard config to the new public IP address

Revision #3
Created 2023-10-01 06:58:34 UTC by Admin
Updated 2023-10-01 07:06:41 UTC by Admin